

## 2. Specifications

### 2.1 Specification Sheet

Model			ASH-24BIS2	
Product Code			CB466000302/CB466000303/CB466000304/CB466000305 CB437002800	
Power Supply	Rated Voltage	V~	220-240	
	Rated Frequency	Hz	50/60	
	Phases		1	
Power Supply Mode			Outdoor	
Cooling Capacity		W	7034	
Heating Capacity		W	7034	
Cooling Power Input		W	1850	
Heating Power Input		W	1750	
Cooling Power Current		A	11	
Heating Power Current		A	10.76	
Rated Input		W	3700	
Rated Current		A	/	
Air Flow Volume(SH/H/M/L/SL)		m <sup>3</sup> /h	1250/1100/950/850/-	
Dehumidifying Volume		L/h	2	
EER		W/W	3.8	
COP		W/W	4	
SEER		W/W	6.5	
HSPF		W/W	/	
Application Area		m <sup>2</sup>	32-50	
Indoor Unit	Model of indoor unit		ASH-24BIS2	
	Indoor Unit Product Code		CB466N00302/CB466N00303/CB466N00304/CB466N00305 CB437N02800	
	Fan Type		Cross-flow	
	Diameter Length(DXL)		mm	Φ106X890
	Fan Motor Cooling Speed		r/min	1250/1100/1000/950/900/850/800/600
	Fan Motor Heating Speed		r/min	1400/1250/1100/1050/1000/900/850/-
	Output of Fan Motor		W	70
	Fan Motor RLA		A	0.38
	Fan Motor Capacitor		μF	/
	Input of Heater		W	/
	Evaporator Form			Aluminum Fin-copper Tube
	Pipe Diameter		mm	Φ7
	Row-fin Gap		mm	2-1.5
	Coil Length (LXDXW)		mm	845X25.4X381
	Swing Motor Model			MP35CJ
	Output of Swing Motor		W	2.5
	Fuse		A	3.15
	Sound Pressure Level (SH/H/M/L/SL)		dB (A)	50/46/43/41/39/37/35/27
	Sound Power Level (SH/H/M/L/SL)		dB (A)	64/60/57/55/53/51/49/41
	Dimension (WXHXD)		mm	1101X327X249
Dimension of Carton Box (LXWXH)		mm	1164X402X339	
Dimension of Package (LXWXH)		mm	1167X405X354	
Net Weight		kg	16.5	
Gross Weight		kg	20	