

| | | | |
|--|---|-------------------|----------------------------------|
| Outdoor Unit | Outdoor Unit Model | | SOH-13BIT |
| | Outdoor Unit Product Code | | CB363W03600 |
| | Compressor Manufacturer | | ZHUHAI LANDA COMPRESSOR CO., LTD |
| | Compressor Model | | FTz-AN108ACBD |
| | Compressor Oil | | FW68DA or equivalent |
| | Compressor Type | | Rotary |
| | Compressor LRA. | A | / |
| | Compressor RLA | A | 4.4 |
| | Compressor Power Input | W | / |
| | Compressor Overload Protector | | / |
| | Throttling Method | | Electron expansion valve |
| | Set Temperature Range | °C | 16~30 |
| | Cooling Operation Ambient Temperature Range | °C | -15~50 |
| | Heating Operation Ambient Temperature Range | °C | -25~30 |
| | Condenser Form | | Aluminum Fin-copper Tube |
| | Condenser Pipe Diameter | mm | Φ7.94 |
| | Condenser Rows-fin Gap | mm | 1-1.2 |
| | Condenser Coil Length (LXDXW) | mm | 666×19.05×527 |
| | Fan Motor Speed | rpm | 900 |
| | Fan Motor Power Output | W | 30 |
| | Fan Motor RLA | A | 0.4 |
| | Fan Motor Capacitor | μF | / |
| | Outdoor Unit Air Flow Volume | m ³ /h | 1950 |
| | Fan Type | | Axial-flow |
| | Fan Diameter | mm | 400 |
| | Defrosting Method | | Automatic Defrosting |
| | Climate Type | | T1 |
| | Isolation | | I |
| | Moisture Protection | | IPX4 |
| | Permissible Excessive Operating Pressure for the Discharge Side | MPa | 4.3 |
| | Permissible Excessive Operating Pressure for the Suction Side | MPa | 2.5 |
| | Sound Pressure Level (H/M/L) | dB (A) | 52 |
| Sound Power Level (H/M/L) | dB (A) | 63 | |
| Dimension(WXHXD) | mm | 732X555X330 | |
| Dimension of Carton Box (LXWXH) | mm | 791X373X590 | |
| Dimension of Package(LXWXH) | mm | 794X376X605 | |
| Net Weight | kg | 24.5 | |
| Gross Weight | kg | 27 | |
| Refrigerant | | R32 | |
| Refrigerant Charge | kg | 0.57 | |
| Connection Pipe | Connection Pipe Length | m | 5 |
| | Connection Pipe Gas Additional Charge | g/m | 16 |
| | Outer Diameter Liquid Pipe | | 1/4" |
| | Outer Diameter Gas Pipe | | 3/8" |
| | Max Distance Height | m | 10 |
| | Max Distance Length | m | 15 |
| Note: The connection pipe applies metric diameter. | | | |

The above data is subject to change without notice. Please refer to the nameplate of the unit.