

Model			SIH+SOH-13BITx
Power Supply		Rated Voltage	V~ 220-240
		Rated Frequency	Hz 50
		Phases	1
Power Supply Mode			Outdoor
Cooling Capacity		W	3510
Heating Capacity		W	3810
Cooling Power Input		W	962
Heating Power Input		W	953
Cooling Current Input		A	4.3
Heating Current Input		A	4.6
Rated Input		W	1550
Rated Cooling Current		A	6.2
Rated Heating Current		A	6.9
Air Flow Volume		m ³ /h	700/650/600/540/480/420/360/0
Dehumidifying Volume		L/h	1.4
EER		W/W	3.65
COP		W/W	4
SEER		W/W	7.1
SCOP(Average/WarmerColder)		W/W	4.1/5.2/3.1
Application Area		m ²	16-24
Indoor Unit	Model		SIH-13BITW/S/C/B
	Product Code		CB497N15800/CB497N15802 CB497N15809/CB497N15803
	Fan Type		Cross-flow
	Fan Diameter Length(DXL)		mm Φ98×633.5
	Cooling Speed		r/min 1350/1200/1100/1000/920/850/800
	Heating Speed		r/min 1300/1200/1120/1050/980/900/850
	Fan Motor Power Output		W 20
	Fan Motor RLA		A 0.31
	Fan Motor Capacitor		μF 1.5
	Evaporator Form		Aluminum Fin-copper Tube
	Evaporator Pipe Diameter		mm Φ5
	Evaporator Row-fin Gap		mm 2-1.4
	Evaporator Coil Length (LXDXW)		mm 635×22.8×306.3
	Swing Motor Model		MP24EB/MP24HF
	Swing Motor Power Output		W 1.5/1.5
	Fuse Current		A 3.15
	Sound Pressure Level		dB (A) Cooling:42/38/35/32/29/27/25 Heating:42/38/36/34/32/30/28
	Sound Power Level		dB (A) Cooling:57/50/47/44/41/39/37 Heating:52/48/46/44/42/40/38
	Dimension (WXHxD)		mm 889X294X212
	Dimension of Carton Box (LXWXH)		mm 935X349X273
Dimension of Package (LXWXH)		mm 940X365X284	
Net Weight		kg 11	
Gross Weight		kg 13	