

**HIGH-STATIC DUCT**
**HIGH-STATIC DUCT Performance data with Big DI Inverter Series 1 3Ph**

Outdoor unit	RAV-GM2241AT8-E1		RAV-GM2801AT8-E1
Indoor unit (High Static duct)	RAV-RM2241DTP-E2		RAV-RM2801DTP-E2
<b>Cooling capacity</b>	<b>kW</b>	<b>19.0</b>	<b>22.5</b>
Cooling range (min. - max.)	kW	4.6 - 22.4	4.6 - 27.0
Power input (min. - rated - max.)	kW C	1.27 - 5.35 - 9.05	1.27 - 6.76 - 11.87
EER	W/W	3.24	2.82
SEER		5.82	5.49
Energy efficiency class	C	-	-
Seasonal electricity consumption	kWh/a C	2468	2928
<b>Heating capacity</b>	<b>kW</b>	<b>22.4</b>	<b>27.0</b>
Heating range (min. - max.)	kW	4.6 - 25.0	4.6 - 31.5
Power input (min. - rated - max.)	kW H	1.27 - 5.71 - 10.15	1.27 - 7.52 - 13.83
COP	W/W	3.92	3.59
SCOP		3.78	3.69
Energy efficiency class	H	-	-
Seasonal electricity consumption	kWh/a H	7174	8136

**HIGH-STATIC DUCT Physical data indoor**

Indoor unit		RAV-RM2241DTP-E2	RAV-RM2801DTP-E2
Air flow	m <sup>3</sup> /h - l/s	3800 - 1055	4800 - 1333
Sound pressure level (back)	dB(A)	44	46
Sound power level (back)	dB(A)	79	81
Dimensions (HxWxD)	mm	448 x 1400 x 900	448 x 1400 x 900
Weight	kg	97	97
Upper limit/middle/standard	Pa	250/150/50	250/150/50

C: cooling mode  
H: heating mode