

SMART 4-WAY CASSETTE
SMART 4-WAY CASSETTE Performance data with Super Digital Inverter Series 1

Outdoor unit			RAV-GP561ATW-E	RAV-GP801ATW-E	RAV-GP1101AT-E	RAV-GP1401AT-E1
Indoor unit (Cassette)			RAV-HM561UT-E	RAV-HM801UT-E	RAV-HM1101UT-E	RAV-HM1401UT-E
Cooling capacity	kW		5.0	7.1	10.0	12.5
Cooling range (min. - max.)	kW		1.2 - 5.6	1.9 - 8.0	3.1 - 12.0	3.1 - 14.0
Power input (min. - rated - max.)	kW	C	0.19 - 1.2 - 2.03	0.26 - 1.37 - 2.94	0.56 - 1.90 - 2.80	0.56 - 2.91 - 3.40
EER			4.17	5.18	5.26	4.30
SEER			8.17	9.72	9.25	8.87
Energy efficiency class D→A+++*		C	A++	A+++	A+++	-
Seasonal electricity consumption	kWh/a	C	214	256	378	845
Heating capacity	kW		5.6	8.0	11.2	14.0
Heating range (min. - max.)	kW		0.9 - 8.1	1.3 - 11.3	2.6 - 13.0	2.6 - 16.5
Power input (min. - rated - max.)	kW	H	0.16 - 1.29 - 2.75	0.20 - 1.45 - 3.15	0.41 - 2.18 - 2.98	0.41 - 3.04 - 4.18
COP	W/W		4.34	5.52	5.14	4.61
SCOP			5.02	5.54	5.03	5.00
Energy efficiency class D→A+++*		H	A++	A+++	A++	-
Seasonal electricity consumption	kWh/a	H	1058	1287	2557	2685

SMART 4-WAY CASSETTE Physical data indoor

Indoor unit			RAV-HM561UT-E	RAV-HM801UT-E	RAV-HM1101UT-E	RAV-HM1401UT-E
Air flow (h/l)	m ³ /h - l/s		1050/750 - 291/208	1920/810 - 533/225	2250/1050 - 625/292	2250/1170 - 625/325
Sound pressure level (h-m-l)	dB(A)		32-29-26	42-35-27	48-40-31	48-41-33
Sound power level (h-m-l)	dB(A)		48-45-43	56-49-43	61-54-46	61-55-48
Dimensions (HxWxD)	mm		256 × 840 × 840	319 × 840 × 840	319 × 840 × 840	319 × 840 × 840
Weight	kg		20	25	25	25
Panel			RBC-U41PG(W)-E			
Panel dimensions (HxWxD)	mm		30×950×950	30×950×950	30×950×950	30×950×950
Panel weight	kg		5	5	5	5

C: cooling mode
H: heating mode
h-m-l: high - medium - low speed

(* The energy efficiency class range of this product category is D→A+++)