

COMPACT 4-WAY CASSETTE

COMPACT 4-WAY CASSETTE Performance data with Super Digital Inverter Series 1

Outdoor unit		RAV-GP561ATW-E	
Indoor unit		RAV- HM561MUTP-E	
Cooling capacity	kW	5.0	
Cooling range (min. - max.)	kW	1.2-5.6	
Power input (min. - rated - max.)	kW C	0.19-1.56-1.97	
EER	W/W	3.21	
SEER		6.27	
Energy efficiency class D→A+++*	C	A++	
Seasonal electricity consumption	kWh/a C	279	
Heating capacity	kW	5.6	
Heating range (min. - max.)	kW	0.9-7.0	
Power input (min. - rated - max.)	kW H	0.16-1.60-2.36	
COP	W/W	3.50	
SCOP		4.32	
Energy efficiency class D→A+++*	H	A+	
Seasonal electricity consumption	kWh/a H	1231	

COMPACT 4-WAY CASSETTE Performance data with Digital Inverter Series 2

Outdoor unit		RAV-GM302ATP-E		RAV-GM402ATP-E		RAV-GM562ATP-E	
Indoor unit		RAV-HM301MUTP-E		RAV-HM401MUTP-E		RAV-HM561MUTP-E	
Cooling capacity	kW	2.5		3.6		5.0	
Cooling range (min. - max.)	kW	0.9 - 3.0		0.9 - 4.0		1.5 - 5.6	
Power input (min. - rated - max.)	kW C	0.18 - 0.59 - 0.82		0.18 - 0.90 - 2.00		0.30 - 1.64 - 1.86	
EER	W/W	4.24		4.00		3.05	
SEER		6.86		6.70		6.19	
Energy efficiency class D→A+++*	C	A++		A++		A++	
Seasonal electricity consumption	kWh/a C	128		188		283	
Heating capacity	kW	3.4		4.0		5.3	
Heating range (min. - max.)	kW	0.8 - 4.5		0.8 - 5.0		1.5 - 6.3	
Power input (min. - rated - max.)	kW H	0.17 - 0.76 - 1.40		0.14 - 0.95 - 1.70		0.30 - 1.47 - 2.40	
COP	W/W	4.47		4.21		3.61	
SCOP		4.73		4.46		4.4	
Energy efficiency class D→A+++*	H	A++		A+		A+	
Seasonal electricity consumption	kWh/a H	681		848		891	

COMPACT 4-WAY CASSETTE Physical data indoor

Indoor unit		RAV-HM301MUTP-E		RAV-HM401MUTP-E		RAV-HM561MUTP-E	
Air Flow (h/l)	m³/h - l/s	640/440 - 177/122		660/468 - 183/130		798/546 - 221/152	
Sound pressure level (h-m-l)	dB(A)	38 - 36 - 30		41 - 36 - 32		44 - 39 - 35	
Sound power level (h-m-l)	dB(A)	53 - 51 - 45		56 - 51 - 47		59 - 54 - 50	
Dimensions (HxWxD)	mm	256 x 575 x 575		256 x 575 x 575		256 x 575 x 575	
Weight	kg	16		16		16	
Panel		RBC-UM21P-E (white) / RBC-UM21PB-E (black)					
Panel Dimensions (HxWxD)	mm	12 x 620 x 620		12 x 620 x 620		12 x 620 x 620	
Panel weight	kg	2.5		2.5		2.5	

C: cooling mode
H: heating mode
h-m-l: high - medium - low speed

(*) The energy efficiency class range of this product category is D→A+++