

COMPACT 1-WAY CASSETTE
COMPACT 1-WAY CASSETTE Performance data with Digital Inverter Series 2 1Ph

Outdoor unit		RAV-GM302ATP-E	RAV-GM402ATP-E
Indoor unit (4-way Cassette)		RAV-HM301U1TP-E	RAV-HM401U1TP-E
Cooling capacity	kW	2.50	3.60
Cooling range (min. - max.)	kW	0.90 - 3.00	0.90 - 4.00
Power input (min. - rated - max.)	kW C	0.19 - 0.69 - 0.92	0.23 - 1.13 - 1.40
EER	W/W	3.62	3.19
SEER		6.20	6.00
Energy efficiency class D→A+++*	C	A++	A+
Seasonal electricity consumption	kWh/a C	141	210
Heating capacity	kW	3.40	4.00
Heating range (min. - max.)	kW	0.80 - 4.50	0.80 - 5.00
Power input (min. - rated - max.)	kW H	0.16 - 1.03 - 1.50	0.18 - 1.32 - 2.00
COP	W/W	3.30	3.03
SCOP		4.10	4.00
Energy efficiency class D→A+++*	H	A++	A+
Seasonal electricity consumption	kWh/a H	888	945

COMPACT 1-WAY CASSETTE Physical data indoor

Indoor unit		RAV-HM301U1TP-E	RAV-HM401U1TP-E
Air Flow (h/l)	m ³ /h - l/s	520/310 - 291/217	540/290 - 341/225
Sound pressure level (h-m-l)	dB(A)	39-35-30	40-36-30
Sound power level (h-m-l)	dB(A)	54-49-45	55-51-45
Dimensions (HxWxD)	mm	150 × 990 × 450	150 × 990 × 450
Weight	kg	13	13
Panel		RBC-UY32P-E	
Panel dimensions (HxWxD)	mm	30 × 1220 × 530	30 × 1220 × 530
Panel weight	kg	4.0	4.0

C: cooling mode
H: heating mode
h-m-l: high - medium - low speed

(*) The energy efficiency class range of this product category is D→A+++