

STANDARD DUCT

STANDARD DUCT Performance data with Super Digital Inverter Series 1 1Ph & 3Ph

Outdoor unit	RAV-	GP561ATW-E	GP801ATW-E	GP1101AT-E	GP1401AT-E1	GP1101AT8-E	GP1401AT8-E	GP1601AT8-E
Indoor unit	RAV-	HM561BTP-E	HM801BTP-E	HM1101BTP-E	HM1401BTP-E	HM1101BTP-E	HM1401BTP-E	HM1601BTP-E
Cooling capacity	kW	5.0	7.1	10.0	10.0	12.5	12.5	14.0
Cooling range (min. - max.)	kW	1.2 - 5.6	1.9 - 8.0	3.1 - 12.0	2.6 - 12.0	3.1 - 14.0	2.6 - 14.0	2.6 - 16.0
Power input (min. - rated - max.)	kW	C 0.19 - 1.52 - 1.99	0.26 - 1.63 - 3.20	0.65 - 2.40 - 3.63	0.66 - 2.58 - 4.01	0.65 - 3.57 - 3.97	0.66 - 3.81 - 4.89	0.66 - 4.49 - 6.50
EER		3.29	4.36	4.17	3.88	3.50	3.28	3.12
SEER		5.81	7.86	7.19	6.10	6.77	6.02	5.81
Energy efficiency class D→A+++*	C	A+	A++	A++	A+	-	-	-
Seasonal electricity consumption	kWh/a	C 301	316	486	574	1107	1245	1444
Heating capacity	kW	5.6	8.0	11.2	11.2	14.0	14.0	16.0
Heating range (min. - max.)	kW	0.9-7.4	1.3 - 11.3	2.6 - 13.0	2.4 - 15.6	2.6 - 16.5	2.4 - 18.0	2.4 - 19.0
Power input (min. - rated - max.)	kW	H 0.16 - 1.61 - 2.76	0.20 - 1.85 - 3.55	0.47 - 2.73 - 3.38	0.53 - 2.76 - 4.42	0.47 - 3.63 - 4.43	0.53 - 3.66 - 5.71	0.53 - 4.57 - 6.96
COP	W/W	3.48	4.32	4.10	4.06	3.86	3.83	3.50
SCOP		4.27	4.85	4.30	4.19	4.29	3.99	3.96
Energy efficiency class D→A+++*	H	A+	A++	A+	A+	-	-	-
Seasonal electricity consumption	kWh/a	H 1245	1472	2997	3606	3133	4143	4238

STANDARD DUCT Performance data with Digital Inverter Series 2 1Ph & 3Ph

Outdoor unit	RAV-	GM562ATP-E	GM802ATW-E	GM902ATW-E	GM1102ATW-E	GM1102AT8W-E	GM1402ATW-E	GM1402AT8W-E	GM1602ATW-E	GM1602AT8W-E
Indoor unit	RAV-	HM561BTP-E	HM801BTP-E	HM901BTP-E	HM1101BTP-E	HM1101BTP-E	HM1401BTP-E	HM1401BTP-E	HM1601BTP-E	HM1601BTP-E
Cooling capacity	kW	5.0	6.7	8.0	9.5	9.5	12.1	12.1	14.0	14.0
Cooling range (min. - max.)	kW	1.5 - 5.6	1.9 - 8.0	1.9 - 8.8	3.0 - 11.2	3.0 - 11.2	3.0 - 13.2	3.0 - 13.2	3.0 - 15.0	3.0 - 15.0
Power input (min. - rated - max.)	kW	C 0.31 - 1.83 - 2.05	0.33 - 2.02 - 2.77	0.33 - 2.39 - 2.97	0.64 - 2.60 - 3.21	0.68 - 2.56 - 3.17	0.64 - 4.01 - 4.52	0.68 - 3.94 - 4.48	0.64 - 5.26 - 6.00	0.68 - 5.14 - 5.90
EER		2.73	3.32	3.35	3.65	3.71	3.02	3.07	2.66	2.72
SEER		5.80	6.37	6.75	6.40	6.00	6.15	5.87	5.90	5.80
Energy efficiency class D→A+++*	C	A+	A++	A++	A++	A+	-	-	-	-
Seasonal electricity consumption	kWh/a	C 302	368	415	519	554	1180	1236	1423	1448
Heating capacity	kW	5.3	7.7	8.6	11.2	11.2	13.0	13.0	16.0	16.0
Heating range (min. - max.)	kW	1.5 - 6.3	1.6 - 9.0	1.6 - 9.9	3.0 - 13.0	3.0 - 13.0	3.0 - 16.0	3.0 - 16.0	3.0 - 17.0	3.0 - 18.0
Power input (min. - rated - max.)	kW	H 0.31 - 1.62 - 2.47	0.31 - 2.04 - 2.66	0.31 - 2.15 - 2.67	0.74 - 2.91 - 3.42	0.78 - 2.87 - 3.38	0.74 - 3.55 - 4.62	0.78 - 3.50 - 4.58	0.74 - 4.73 - 5.64	0.78 - 4.66 - 6.92
COP	W/W	3.27	3.77	4.00	3.85	3.90	3.66	3.71	3.38	3.43
SCOP		4.11	4.30	4.30	4.00	3.92	3.92	3.84	4.05	3.96
Energy efficiency class D→A+++*	H	A+	A+	A+	A+	A	-	-	-	-
Seasonal electricity consumption	kWh/a	H 954	1660	2050	2937	2999	2998	3061	2901	2966

STANDARD DUCT Performance data with Digital Inverter Classic Series 1 1Ph & 3Ph

Outdoor unit	RAV-	GV561ATP-E	GV801ATP-E	GV1101ATP-E	GV1101AT8P-E	GV1401ATP-E	GV1401AT8P-E	GV1601ATP-E	GV1601AT8P-E
Indoor unit	RAV-	HM561BTP-E	HM801BTP-E	HM1101BTP-E	HM1101BTP-E	HM1401BTP-E	HM1401BTP-E	HM1601BTP-E	HM1601BTP-E
Cooling capacity	kW	5.0	6.7	9.5	9.5	11.5	12.1	13.0	13.0
Cooling range (min. - max.)	kW	1.5-5.6	1.5-8.0	3.0-11.2	3.0-11.2	3.0-12.0	3.0-14.0	3.0-14.0	3.0-15.0
Power input (min. - rated - max.)	kW	C 1.85	2.30	3.17	3.06	4.70	4.90	5.40	5.40
EER		2.70	2.91	3.00	3.10	2.45	2.47	2.41	2.41
SEER		5.20	5.1	5.1	5.3	5.1	5.1	4.90	4.90
Energy efficiency class D→A+++*	C	A	A	A	A	A	-	-	-
Seasonal electricity consumption	kWh/a	C 336	460	652	628	789	1423	1590	1591
Heating capacity	kW	5.3	7.0	10.0	10.0	11.9	12.3	13.5	13.5
Heating range (min. - max.)	kW	1.5-6.3	1.5-9.0	3.0-13.0	3.0-13.0	3.0-16.0	3.0-16.0	3.0-18.0	3.0-18.0
Power input (min. - rated - max.)	kW	H 1.65	2.33	3.00	2.94	3.90	4.10	4.00	4.00
COP	W/W	3.21	3.0	3.3	3.40	3.05	3.00	3.38	3.38
SCOP		3.90	4.00	3.80	3.80	3.80	3.80	4.15	4.15
Energy efficiency class D→A+++*	H	A	A+	A	A	A	-	-	-
Seasonal electricity consumption	kWh/a	H 1005	1680	2800	2800	2874	2874	2700	2693

STANDARD DUCT Physical data indoor

Indoor unit	RAV-	HM561BTP-E	HM801BTP-E	HM901BTP-E	HM1101BTP-E	HM1401BTP-E	HM1601BTP-E
Air flow (h/l)	m³/h - l/s	800/480 - 222/133	1200/750 - 333/208	1700/1000 - 472/278	2100/1260 - 583/350	2100/1260 - 583/350	2100/1260 - 583/350
Sound pressure level (h-m-l)*	dB(A)	33-29-25	34-30-26	37-33-30	40-36-33	40-36-33	40-36-33
Sound power level (h-m-l)**	dB(A)	55-51-46	55-51-46	60-55-51	63-58-54	63-58-54	63-58-54
Dimensions (HxWxD)	mm	275 x 700 x 750	275 x 1000 x 750	275 x 1400 x 750	275 x 1400 x 750	275 x 1400 x 750	275 x 1400 x 750
Weight	kg	23	31	41	41	41	41
External static pressure (stand/upper limit)	Pa	30/150	30/150	40/150	40/150	50/150	50/150

C: cooling mode
H: heating mode
h-m-l: high - medium - low speed
*bottom air inlet
**back air inlet

(*) The energy efficiency class range of this product category is D→A+++

LIGHT COMMERCIAL